



www.miko-plast.com

KONGSVEIEN 94 N-1177 OSLO NORWAY

TELEPHONE : + 47 23 38 47 73
TELEFAX : + 47 23 38 47 71
ENTERPRISE NO: 980 030 628

Miko Edge Protector HD™

Art.no: KB-374-003

Doc. 8:18

PRODUCT DATA:

Dimension 160x120x136mm
Tolerance +/- 1 mm
Angel 85°
Tolerance +/- 5°
Weight 370 gram
Material PP
Alternative material PEHD
Colour Unspecified.

USE:

Temperature range +40°C to - 30°C

PACKAGING:

Packing Pallet
Number each pallet 576 pcs
Number each transport unit (Two pallets) 1152 pcs
Net weight each pallet 235 kg

MATERIAL RECYCLING DATA HDPE:

Density ISO1183 962 kg/m³
Melt index 190°C/2,16 kg ISO 1133 12 g/10min
Tensile strength ISO 527-2 1150 Mpa
Surface hardness ISO 868 62 Shore D
Heat deflection ISO 75-2 73°C
Impact strength ISO 8256*/A1 50 KJ/m²

Certification:

Dekra / Fraunhofer certified method of lashing and securing.
Pb. Nr. 226/1605/702073/181-6350824